

Year:	2015
Model:	J-585
Size:	91" x 91" x 37.5" Front/42" Side (231 cm x 231 cm x 92 cm Front/107 cm Back)
Series:	J-500
Board:	J500 Series ProTouch™ Glass Board: 6600-885 with microprocessor
Transformer:	N/A on the circuit board
Heater:	Heater: 5.5 kW 240 VAC Hi-Flow 6500-843
Panel:	Control Panel: LCD J500 ProTouch Glass color graphics 6600-100
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Temperature Sensor 6600-751
Hi-Limit:	Hi-Limit Sensor 6472-525 (2-pin harness)
Flow Switch:	Flow switch with clear tee 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 48F 6500-907
53 Total Jets:	3 - MX2 (2540-367, 6541-133), 6 - NX2 (6540-815), 8 - RX2 (6541-288), 2 - PX (6541-561, 6541-562, 6541-563), 2 - FX Directional (6541-261), 8 - FX Small (6541-117), 10 - FX Rotational (6541-031), 5 - FX Large Rotational (6541-132)
Air Controls:	4-on/off air toggle control (6541-142)
Diverter:	2 diverter valves with knob and mounting nut (6541-826), o-ring (2x 6540-511)
Filter:	1-60 ft ² (6000-383AJ), 1-40 ft ² (6473-157J), 1-Spun bound (6473-161J) Debris attachment bag: 6570-398

Year:	2015
Model:	J-575
Size:	91" x 91" x 37.5" Front/42" Side (231 cm x 231 cm x 92 cm Front/107 cm Back)
Series:	J-500
Board:	J500 Series ProTouch™ Glass Board: 6600-885 with microprocessor
Transformer:	N/A on the circuit board
Heater:	Heater: 5.5 kW 240 VAC Hi-Flow 6500-843
Panel:	Control Panel: LCD J500 ProTouch Glass color graphics 6600-100
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Temperature Sensor 6600-751
Hi-Limit:	Hi-Limit Sensor 6472-525 (2-pin harness)
Flow Switch:	Flow switch with clear tee 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 48F 6500-907
53 Total Jets:	5 - MX2 (2540-367, 6541-133), 6 - NX2 (6540-815), 6 - RX2 (6541-288), 8 - PX (6541-561, 6541-562, 6541-563), 2 - FX Directional (6541-261), 6 - FX Small (6541-117), 14 - FX Rotational (6541-031), 6 - FX Large Rotational (6541-132)
Air Controls:	4-on/off air toggle control (6541-142)
Diverter:	2 diverter valves with knob and mounting nut (6541-826), o-ring (2x 6540-511)
Filter:	1-60 ft ² (6000-383AJ), 1-40 ft ² (6473-157J), 1-Spun bound (6473-161J) Debris attachment bag: 6570-398

Year:	2015
Model:	J-495
Size:	90" x 110" x 41" Front/46" Back (228.6 cm x 279.4 cm x 104.14 cm Front/116 cm Back)
Series:	J-400
Board:	J-1000 Control System Controller: 6600-400 (Entire controller is changed instead of the circuit board)
Transformer:	N/A Entire controller is changed instead of the circuit board
Heater:	Heater: 5.5 kW 240 VAC Hi-Flow DSMT (Nuts and gaskets included) 6500-417
Panel:	Control Panel: LCD 1/3 VGA color graphics, 3-Pump 60 Hz (6600-099) Wireless RF remote control with LCD display (6560-304); Harness: Topside control panel to main load box (6560-956)
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #3:	2.5 HP 1-SP 240V NB 56F pump (6500-363) Universal mounting bracket kit (6000-535)
Temp Sensor:	Temperature Sensor with DSMT connector cable, resistance can be checked 6600-181
Hi-Limit:	Hi-Limit Sensor with DSMT connector cable, resistance can be checked 6600-179
Flow Switch:	Flow switch assembly with DSMT connector cable 6560-651
Circulation Pump:	Pump: Circmaster 230V 60HZ 48F 6500-907
62 Total Jets:	3-MX2 (2540-367, 6541-133), 10-NX2 (6540-815), 11-RX2 (6541-288), 18-FX (6541-170), 8-FX Small (6541-117), 6-FX Rotational (6541-031), 5-FX Large Rotational (6541-132), 1-IX (6560-103)
Air Controls:	5-Knob (20101-001), 5-Body and stem (6540-377)
Diverter:	2 (3-way diverter) - Knob (2540-533), Cap (6540-729), stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	1-75 ft ² (6540-164J), 1-40 ft ² (6473-157J), 1-Spun bound (6473-161J) Debris attachment bag: 6570-398

Year:	2015
Model:	J-480
Size:	94" x 94" x 39" Front/44" Back (239 cm x 239 cm x 99 cm Front/112 cm Back)
Series:	J-400
Board:	J-1000 Control System Controller: 6600-401 (Entire controller is changed instead of the circuit board)
Transformer:	N/A Entire controller is changed instead of the circuit board
Heater:	Heater: 5.5 kW 240 VAC Hi-Flow DSMT (Nuts and gaskets included) 6500-417
Panel:	Control Panel: LCD 1/3 VGA color graphics, 3-Pump 60 Hz (6600-099) Wireless RF remote control with LCD display (6560-304); Harness: Topside control panel to main load box (6560-956)
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-365) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Temperature Sensor with DSMT connector cable, resistance can be checked 6600-181
Hi-Limit:	Hi-Limit Sensor with DSMT connector cable, resistance can be checked 6600-179
Flow Switch:	Flow switch assembly with DSMT connector cable 6560-651
Circulation Pump:	Pump: Circmaster 230V 60HZ 48F 6500-907
52 Total Jets:	3-MX2 (2540-367, 6541-133), 4-NX2 (6540-815), 6-RX (6541-288), 6-PX (6541-561, 6541-562, 6541-563), 12-FX (6541-170), 8-FX Small (6541-117), 6-FX Rotational (6541-031), 6-FX Large Rotational (6541-132), 1-IX (6560-103)
Air Controls:	4-Knob (20101-001), 4-Body and stem (6540-377)
Diverter:	2 (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	1-75 ft ² (6540-164J), 1-40 ft ² (6473-157J), 1-Spun bound (6473-161J) Debris attachment bag: 6570-398

Year:	2015
Model:	J-470
Size:	91" x 91" x 39" Front/44" Back (231 cm x 231 cm x 99 cm Front/112 cm Back)
Series:	J-400
Board:	J-1000 Control System Controller: 6600-401 (Entire controller is changed instead of the circuit board)
Transformer:	N/A Entire controller is changed instead of the circuit board
Heater:	Heater: 5.5 kW 240 VAC Hi-Flow DSMT (Nuts and gaskets included) 6500-417
Panel:	Control Panel: LCD 1/3 VGA color graphics, 2-Pump 60 Hz (6600-099) Wireless RF remote control with LCD display (6560-304); Harness: Topside control panel to main load box (6560-956)
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-365) Universal mounting bracket kit (6000-535)
Temp Sensor:	Temperature Sensor with DSMT connector cable, resistance can be checked 6600-181
Hi-Limit:	Hi-Limit Sensor with DSMT connector cable, resistance can be checked 6600-179
Flow Switch:	Flow switch assembly with DSMT connector cable 6560-651
Circulation Pump:	Pump: Circmaster 230V 60HZ 48F 6500-907
43 Total Jets:	3-MX2 (2540-367, 6541-133), 4-NX2 (6540-815), 6-RX2 (6541-288), 10-FX (6541-170), 8-FX Small (6541-117), 6-FX Rotational (6541-031), 5-FX Large Rotational (6541-132), 1-IX (6560-103)
Air Controls:	4-Knob (20101-001), 4-Body and stem (6540-377)
Diverter:	2 (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	1-75 ft ² (6540-164J), 1-40 ft ² (6473-157J), 1-Spun bound (6473-161J) Debris attachment bag: 6570-398

Year:	2015
Model:	J-465
Size:	88" x 88" x 39" Front/43" Back (223.5 cm x 223.5 cm x 99 cm Front/109 cm Back)
Series:	J-400
Board:	J-1000 Control System Controller: 6600-401 (Entire controller is changed instead of the circuit board)
Transformer:	N/A Entire controller is changed instead of the circuit board
Heater:	Heater: 5.5 kW 240 VAC Hi-Flow DSMT (Nuts and gaskets included) 6500-417
Panel:	Control Panel: LCD 1/3 VGA color graphics, 2-Pump 60 Hz (6600-099) Wireless RF remote control with LCD display (6560-304); Harness: Topside control panel to main load box (6560-956)
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-365) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Temperature Sensor with DSMT connector cable, resistance can be checked 6600-181
Hi-Limit:	Hi-Limit Sensor with DSMT connector cable, resistance can be checked 6600-179
Flow Switch:	Flow switch assembly with DSMT connector cable 6560-651
Circulation Pump:	Pump: Circmaster 230V 60HZ 48F 6500-907
39 Total Jets:	5-MX2 (2540-367, 6541-133), 4-NX2 (6540-815), 4-PX (6541-561, 6541-562, 6541-563), 6-RX2 (6541-288), 6-FX (6541-170, 6-FX Rotational (6541-031), 7-FX Large Rotational (6541-132), 1-IX (6560-103)
Air Controls:	3-Knob (20101-001), 3-Body and stem (6540-377)
Diverter:	2-(3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	1-75 ft ² (6540-164J), 1-40 ft ² (6473-157J), 1-Spun bound (6473-161J) Debris attachment bag: 6570-398

Year:	2015
Model:	J-425
Size:	76" x 87" x 34" Front/39" Back (193.04 cm x 220.08 cm x 86.36 cm Front/99.06 cm Back)
Series:	J-400
Board:	J-1000 Control System Controller: 6600-401 (Entire controller is changed instead of the circuit board)
Transformer:	N/A Entire controller is changed instead of the circuit board
Heater:	Heater: 5.5 kW 240 VAC Hi-Flow DSMT (Nuts and gaskets included) 6500-417
Panel:	Control Panel: LCD 1/3 VGA color graphics, 2-Pump 60 Hz (6600-099) Wireless RF remote control with LCD display (6560-304); Harness: Topside control panel to main load box (6560-956)
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Temperature Sensor with DSMT connector cable, resistance can be checked 6600-181
Hi-Limit:	Hi-Limit Sensor with DSMT connector cable, resistance can be checked 6600-179
Flow Switch:	Flow switch assembly with DSMT connector cable 6560-651
Circulation Pump:	Pump: Circmaster 230V 60HZ 48F 6500-907
27 Total Jets:	3-MX2 (2540-367, 6541-133), 2-NX2 (6540-815), 2-RX2 (6541-288), 10-FX (6541-170), 4-FX Rotational (6541-01), 5-FX Large Rotational (6541-132), 1-IX (6560-103)
Air Controls:	4-Knob (20101-001), 4-Body and stem (6540-377)
Diverter:	1-(3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	1-75 ft ² (6540-164J), 1-40 ft ² (6473-157J), 1-Spun bound (6473-161J) Debris attachment bag: 6570-398

Year:	2015
Model:	J-415
Size:	76" x 66" x 32" (193.04 cm x 167.64 cm x 81.28 cm)
Series:	J-400
Board:	J-1000 Control System Controller: 6600-401 (Entire controller is changed instead of the circuit board)
Transformer:	N/A Entire controller is changed instead of the circuit board
Heater:	Heater: 5.5 kW 240 VAC Hi-Flow DSMT (Nuts and gaskets included) 6500-417
Panel:	Control Panel: LCD 1/3 VGA color graphics, 1-Pump 60 Hz (6600-099) Wireless RF remote control with LCD display (6560-304); Harness: Topside control panel to main load box (6560-956)
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-363) Universal mounting bracket kit (6000-535)
Temp Sensor:	Temperature Sensor with DSMT connector cable, resistance can be checked 6600-181
Hi-Limit:	Hi-Limit Sensor with DSMT connector cable, resistance can be checked 6600-179
Flow Switch:	Flow switch assembly with DSMT connector cable 6560-651
Circulation Pump:	Pump: Circmaster 230V 60HZ 48F 6500-907
21 Total Jets:	2-NX2 (6540-815), 5-RX2 (6541-288), 9-FX (6541-170), 4-FX Rotational (6541-031), 1-FX Large Rotational (6541-132)
Air Controls:	2-Knob (20101-001), 2-Body and stem (6540-377)
Diverter:	1-(3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	1-75 ft ² (6540-164J), 1-40 ft ² (6473-157J), 1-Spun bound (6473-161J) Debris attachment bag: 6570-398

Year:	2015
Model:	J-LXL
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	L-LX
Board:	J-LX Series LED circuit board Board: 6600-726 Micro Chip: 6660-285 Rev. 3.61
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-LX LED SMT 2-Pump with cable to DCU (MiniDin) 6600-506
Pump #1:	2.5 HP 2-SP 240V NB 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
38 Total Stainless Steel Jets (Standard):	2-MX2 (2540-367, 6541-133), 6-NX2 (6540-815), 4-RX2 (6541-288), 23-FX (6541-170), 3-FX Large Rotational (6541-132)
Air Controls:	3 - on/off air toggle control (6541-142)
Diverter:	1 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-75 ft ² (6540-164J), 1-Skimmer Weir Filter (6540-188) Debris attachment bag: 6570-392

Year:	2015
Model:	J-LX
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	L-LX
Board:	J-LX Series LED circuit board Board: 6600-726 Micro Chip: 6660-285 Rev. 3.61
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-LX SMT LED 2-Pump with cable to DCU (MiniDin) 6600-506
Pump #1:	2.5 HP 2-SP 240V NB 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
36 Total Stainless Steel Jets (Standard):	2-MX2 (2540-367, 6541-133), 4-NX2 (6540-815), 4-RX2 (6541-288), 21-FX (6541-170), 5-FX Large Rotational (6541-132)
Air Controls:	4 - on/off air toggle control (6541-142)
Diverter:	1 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-75 ft ² (6540-164J), 1-Skimmer Weir Filter (6540-188) Debris attachment bag: 6570-392

Year:	2015
Model:	J-385
Size:	91" x 91" x 38" (231 cm x 231 cm x 96.5 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-293 Micro Chip: 6660-289 Rev. 3.82
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-300 LED 2-Pump with cable to DCU (MiniDin) 6600-175
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
49 Total Stainless Steel Jets (Standard):	3-MX2 (2540-367, 6541-133), 2-BX (6541-231), 4-NX2 (6540-815), 17-FX (20285-001), 8-FX Small (6541-117), 7-FX Rotational (6541-031), 4-FX Large (6541-118), 4-FX Large Rotational (6541-132)
Air Controls:	4 - on/off air toggle control (6541-142)
Diverter:	2 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

Year:	2015
Model:	J-375
Size:	91" x 91" x 38" (231 cm x 231 cm x 96.5 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-293 Micro Chip: 6660-289 Rev. 3.82
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-300 LED 2-Pump with cable to DCU (MiniDin) 6600-175
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
50 Total Stainless Steel Jets (Standard):	5-MX2 (2540-367, 6541-133), 12-BX (6541-231), 4-NX2 (6540-815), 18-FX (20285-001), 6-FX Rotational (6541-031), 2-FX Large (6541-118), 3-FX Large Rotational (6541-132)
Air Controls:	4 - on/off air toggle control (6541-142)
Diverter:	2 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

Year:	2015
Model:	J-365
Size:	91" x 84" x 38" (231 cm x 213.5 cm x 96.5 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-293 Micro Chip: 6660-289 Rev. 3.82
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-300 SMT LED 2-Pump with cable to DCU (MiniDin) 6600-175
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
44 Total Stainless Steel Jets (Standard):	3-MX2 (2540-367, 6541-133), 4-NX2 (6540-815), 19-FX (20285-001), 8-FX Small (6541-117), 4-FX Rotational, 3-FX Large (6541-118), 3-FX Large Rotational (6541-132)
Air Controls:	4 - on/off air toggle control (6541-142)
Diverter:	2 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

Year:	2015
Model:	J-355
Size:	91" x 84" x 38" (231 cm x 213.5 cm x 96.5 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-293 Micro Chip: 6660-289 Rev. 3.82
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-300 LED 2-Pump with cable to DCU (MiniDin) 2600-328
Pump #1:	2.5 HP 2-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
42 Total Stainless Steel Jets (Standard):	5-MX2 (2540-367, 6541-133), 12-BX (6541-231), 2-NX2 (6540-815), 14-FX (20285-001), 4-FX Rotational (6541-031), 2-FX Large (6541-118), 3-FX Large Rotational (6541-132)
Air Controls:	3 - on/off air toggle control (6541-142)
Diverter:	2 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

Year:	2015
Model:	J-345
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-293 Micro Chip: 6660-289 Rev. 3.82
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-300 SMT LED 2-Pump with cable to DCU (MiniDin) 6600-175
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
39 Total Stainless Steel Jets (Standard):	3-MX2 (2540-367, 6541-133), 19-FX (20285-001), 8-FX Small (6541-117), 4-FX Rotational (6541-031), 2-FX Large (6541-118), 3-FX Large Rotational (6541-132)
Air Controls:	4 - on/off air toggle control (6541-142)
Diverter:	2 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

Year:	2015
Model:	J-335
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-293 Micro Chip: 6660-289 Rev. 3.82
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-300 SMT LED 2-Pump with cable to DCU (MiniDin) 6600-175
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
40 Total Stainless Steel Jets (Standard)*:	2-MX2 (2540-367, 6541-133), 12-BX (6541-231), 16-FX (20285-001), 4-FX Rotational (6541-031), 2-FX Large (6541-118), 4-FX Large Rotational (6541-132)
Air Controls:	3 - on/off air toggle control (6541-142)
Diverter:	2 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

Year:	2015
Model:	J-325
Size:	76" x 84" x 34" (193 cm x 213.5 cm x 86.5 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-295 Micro Chip: 6660-289 Rev. 3.82
Transformer:	120V 12V 6560-274 (without plug) 6000-516 (with plug)
Heater:	Heater: 1.0 kW 120V/4.4kW 240 VAC tube heater (convertible) 6500-063 (1-Adapter (6540-034))
Panel:	J-300 SMT LED 1-Pump with cable to DCU (MiniDin) 6600-713
Pump #1:	1.5 HP 2-SP 120V 48F pump (6500-345) Universal mounting bracket kit (6000-532)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with tee fitting 6560-852 (2x 6540-262 adapters)
Circulation Pump:	Pump: Circ E-10 115V 60 Hz 6500-460
21 Total Stainless Steel Jets (Standard):	6-FX (20285-001), 4-FX Small (6541-117), 2-FX Rotational (6541-031), 2-FX Large (6541-118), 7-FX Large Rotational (6541-132)
Air Controls:	4 - on/off air toggle control (6541-142)
Diverter:	1 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

Year:	2015
Model:	J-315
Size:	76" x 66" x 32" (193 cm x 168 cm x 81 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-295 Micro Chip: 6660-289 Rev. 3.82
Transformer:	120V 12V 6560-274 (without plug) 6000-516 (with plug)
Heater:	Heater: 1.0 kW 120V/4.4kW 240 VAC tube heater (convertible) 6500-063 (1-Adapter (6540-034)
Panel:	J-300 SMT LED 1-Pump with cable to DCU (MiniDin) 6600-713
Pump #1:	1.5 HP 2-SP 120V 48F pump (6500-345) Universal mounting bracket kit (6000-532)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with tee fitting 6560-852 (2x 6540-262 adapters)
Circulation Pump:	Pump: Circ E-10 115V 60 Hz 6500-460
21 Total Stainless Steel Jets (Standard):	6-BX (6541-231), 8-FX (20285-001), 2-FX Rotational (6541-031), 5-FX Large Rotational (6541-132)
Air Controls:	3 - on/off air toggle control (6541-142)
Diverter:	1 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

Year:	2015
Model:	J-280
Size:	90" x 90" x 36.5" (228.6 cm x 228.6 cm x 92.7 cm)
Series:	J-200
Board:	J-200 Series LED circuit board Board: 6600-720 Micro Chip: 6660-287 Rev. 5.60
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5kW 240 VAC 6000-156
Panel:	J-200 SMT LED 2-Pump 6600-501
Pump #1:	2.5 HP 2-SP 240V 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Pressure Switch:	Pressure Switch 6560-869
44 Total Stainless Steel Jets (Standard):	8-Classic Direct (2540-265), 16-Classic Euro (2540-255), 7-Classic Luxury (2540-433), 6-Classic Mini (2540-319), 6- Classic Rotational (2472-610), 1-Classic Whirl (2540-529)
Air Controls:	4 - Knob (2540-281), Manifold (6541-284), Nut (6541-282), Gasket (6541-283)
Diverter:	1 - Knob (6540-274), Cap (2540-273), Stem o-ring (2x 6541-241), Body o-ring (6541-240), Gate (6541-242)
Filter:	1-95 ft ² (2540-381J) Debris attachment bag: 6570-392

Year:	2015
Model:	J-275
Size:	90" x 90" x 36.5" (228.6 cm x 228.6 cm x 92.7 cm)
Series:	J-200
Board:	J-200 Series LED circuit board Board: 6600-720 Micro Chip: 6660-287 Rev. 5.60
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5kW 240 VAC 6000-156
Panel:	J-200 SMT LED 2-Pump 6600-501
Pump #1:	2.5 HP 2-SP 240V 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Pressure Switch:	Pressure Switch 6560-869
45 Total Stainless Steel Jets (Standard):	8-Classic Direct (2540-265), 14-Classic Euro (2540-255), 6-Classic Luxury (2540-433), 3-Classic Mini (2540-319), 6-Classic Pulsator (2540-245), 6-Classic Rotational (2472-610), 2-Classic Turbo (6541-652)
Air Controls:	3 - Knob (2540-281), Manifold (6541-284), Nut (6541-282), Gasket (6541-283)
Filter:	1-50 ft ² (373045)

Year:	2015
Model:	J-245
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	J-200
Board:	J-200 Series LED circuit board Board: 6600-720 Micro Chip: 6660-287 Rev. 5.60
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5kW 240 VAC 6000-156
Panel:	J-200 SMT LED 2-Pump 6600-501
Pump #1:	2.5 HP 2-SP 240V 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Pressure Switch:	Pressure Switch 6560-869
35 Total Stainless Steel Jets (Standard):	4-Classic Direct (2540-265), 18-Classic Euro (2540-255), 5-Classic Luxury (2540-433), 2-Classic Mini (2540-319), 4-Classic Rotational (2472-610), 2-Classic Turbo (6541-652)
Air Controls:	3 - Knob (2540-281), Manifold (6541-284), Nut (6541-282), Gasket (6541-283)
Filter:	1-50 ft ² (373045)

Year:	2015
Model:	J-235
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	J-200
Board:	J-200 Series LED circuit board Board: 6600-720 Micro Chip: 6660-287 Rev. 5.60
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5kW 240 VAC 6000-156
Panel:	J-200 SMT LED 2-Pump 6600-501
Pump #1:	2.5 HP 2-SP 240V 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Pressure Switch:	Pressure Switch 6560-869
35 Total Stainless Steel Jets (Standard):	4-Classic Direct (2540-265), 12-Classic Euro (2540-255), 6-Classic Luxury (2540-433), 3-Classic Mini (2540-319), 4-Classic Pulsator (2540-245), 4-Classic Rotational (2472-610), 2-Classic Turbo (6541-652)
Air Controls:	3 - Knob (2540-281), Manifold (6541-284), Nut (6541-282), Gasket (6541-283)
Filter:	1-50 ft ² (373045)

Year:	2015
Model:	J-210
Size:	78" Round x 36" (198 cm Round x 91.5 cm)
Series:	J-200
Board:	J-200 Series LED circuit board Board: 6600-722 Micro Chip: 6660-287 Rev. 5.60
Transformer:	240V 12V 6560-274 (without plug) 6000-516 (with plug)
Heater:	Heater: 1kW 120 VAC/4kW 240V (convertible) 6000-338
Panel:	J-200 SMT LED 1-Pump 6600-500
Pump #1:	1.5 HP 2-SP 120V 48F pump (6500-345) Universal mounting bracket kit (6000-532)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Pressure Switch:	Pressure Switch 6560-869
19 Total Textured Jets (Standard):	4-Classic Direct (2540-261), 4-Classic Luxury (2540-431), 10-Classic Mini (2540-317), 1-Divert-A-Jet (6541-800)
Air Controls:	3 - Knob (2540-281), Manifold (6541-284), Nut (6541-282), Gasket (6541-283)
Filter:	1-50 ft ² (373045)

Year:	2014
Model:	J-480
Size:	94" x 94" x 39" Front/44" Back (239 cm x 239 cm x 99 cm Front/112 cm Back)
Series:	J-400
Board:	J-1000 Control System Controller: 6600-401 (Entire controller is changed instead of the circuit board)
Transformer:	N/A Entire controller is changed instead of the circuit board
Heater:	Heater: 5.5 kW 240 VAC Hi-Flow DSMT (Nuts and gaskets included) 6500-417
Panel:	Control Panel: LCD 1/3 VGA color graphics, 3-Pump 60 Hz (6600-099) Wireless RF remote control with LCD display (6560-304); Harness: Topside control panel to main load box (6560-956)
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-365) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Temperature Sensor with DSMT connector cable, resistance can be checked 6600-181
Hi-Limit:	Hi-Limit Sensor with DSMT connector cable, resistance can be checked 6600-179
Flow Switch:	Flow switch assembly with DSMT connector cable 6560-651
Circulation Pump:	Pump: Circmaster 230V 60HZ 48F 6500-907
52 Total Jets:	3-MX2 (2540-367, 6541-133), 4-NX2 (6540-815), 6-RX2 (6541-288), 6-PX (6541-561, 6541-562, 6541-563), 12-FX (20285-001), 8-FX Small (6541-117), 6-FX Rotational (6541-031), 6-FX Large Rotational (6541-132), 1-IX (6560-103)
Air Controls:	4-Knob (20101-001), 4-Body and stem (6540-377)
Diverter:	2 (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	1-75 ft ² (6540-164J), 1-40 ft ² (6473-157J), 1-Spun bound (6473-161J) Debris attachment bag: 6570-398

Year:	2014
Model:	J-470
Size:	91" x 91" x 39" Front/44" Back (231 cm x 231 cm x 99 cm Front/112 cm Back)
Series:	J-400
Board:	J-1000 Control System Controller: 6600-401 (Entire controller is changed instead of the circuit board)
Transformer:	N/A Entire controller is changed instead of the circuit board
Heater:	Heater: 5.5 kW 240 VAC Hi-Flow DSMT (Nuts and gaskets included) 6500-417
Panel:	Control Panel: LCD 1/3 VGA color graphics, 2-Pump 60 Hz (6600-099) Wireless RF remote control with LCD display (6560-304); Harness: Topside control panel to main load box (6560-956)
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-365) Universal mounting bracket kit (6000-535)
Temp Sensor:	Temperature Sensor with DSMT connector cable, resistance can be checked 6600-181
Hi-Limit:	Hi-Limit Sensor with DSMT connector cable, resistance can be checked 6600-179
Flow Switch:	Flow switch assembly with DSMT connector cable 6560-651
Circulation Pump:	Pump: Circmaster 230V 60HZ 48F 6500-907
43 Total Jets:	3-MX2 (2540-367, 6541-133), 4-NX2 (6540-815), 6-RX2 (6541-288), 10-FX (20285-001), 8-FX Small (6541-117), 6-FX Rotational (6541-031), 5-FX Large Rotational (6541-132), 1-IX (6560-103)
Air Controls:	4-Knob (20101-001), 4-Body and stem (6540-377)
Diverter:	2 (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	1-75 ft ² (6540-164J), 1-40 ft ² (6473-157J), 1-Spun bound (6473-161J) Debris attachment bag: 6570-398

Year:	2014
Model:	J-465
Size:	88" x 88" x 39" Front/43" Back (223.5 cm x 223.5 cm x 99 cm Front/109 cm Back)
Series:	J-400
Board:	J-1000 Control System Controller: 6600-401 (Entire controller is changed instead of the circuit board)
Transformer:	N/A Entire controller is changed instead of the circuit board
Heater:	Heater: 5.5 kW 240 VAC Hi-Flow DSMT (Nuts and gaskets included) 6500-417
Panel:	Control Panel: LCD 1/3 VGA color graphics, 2-Pump 60 Hz (6600-099) Wireless RF remote control with LCD display (6560-304); Harness: Topside control panel to main load box (6560-956)
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-365) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Temperature Sensor with DSMT connector cable, resistance can be checked 6600-181
Hi-Limit:	Hi-Limit Sensor with DSMT connector cable, resistance can be checked 6600-179
Flow Switch:	Flow switch assembly with DSMT connector cable 6560-651
Circulation Pump:	Pump: Circmaster 230V 60HZ 48F 6500-907
39 Total Jets:	5-MX2 (2540-367, 6541-133), 4-NX2 (6540-815), 4-PX (6541-561, 6541-562, 6541-563), 6-RX2 (6541-288), 6-FX (20285-001), 6-FX Rotational (6541-031), 7-FX Large Rotational (6541-132), 1-IX (6560-103)
Air Controls:	3-Knob (20101-001), 3-Body and stem (6540-377)
Diverter:	2-(3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	1-75 ft ² (6540-164J), 1-40 ft ² (6473-157J), 1-Spun bound (6473-161J) Debris attachment bag: 6570-398

Year:	2014
Model:	J-425
Size:	76" x 87" x 34" Front/39" Back (193.04 cm x 220.08 cm x 86.36 cm Front/99.06 cm Back)
Series:	J-400
Board:	J-1000 Control System Controller: 6600-401 (Entire controller is changed instead of the circuit board)
Transformer:	N/A Entire controller is changed instead of the circuit board
Heater:	Heater: 5.5 kW 240 VAC Hi-Flow DSMT (Nuts and gaskets included) 6500-417
Panel:	Control Panel: LCD 1/3 VGA color graphics, 2-Pump 60 Hz (6600-099) Wireless RF remote control with LCD display (6560-304); Harness: Topside control panel to main load box (6560-956)
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Temperature Sensor with DSMT connector cable, resistance can be checked 6600-181
Hi-Limit:	Hi-Limit Sensor with DSMT connector cable, resistance can be checked 6600-179
Flow Switch:	Flow switch assembly with DSMT connector cable 6560-651
Circulation Pump:	Pump: Circmaster 230V 60HZ 48F 6500-907
27 Total Jets:	3-MX2 (2540-367, 6541-133), 2-NX2 (6540-815), 2-RX2 (6541-288), 10-FX (20285-001), 4-FX Rotational (6541-01), 5-FX Large Rotational (6541-132), 1-IX (6560-103)
Air Controls:	4-Knob (20101-001), 4-Body and stem (6540-377)
Diverter:	1-(3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	1-75 ft ² (6540-164J), 1-40 ft ² (6473-157J), 1-Spun bound (6473-161J) Debris attachment bag: 6570-398

Year:	2014
Model:	J-415
Size:	76" x 66" x 32" (193.04 cm x 167.64 cm x 81.28 cm)
Series:	J-400
Board:	J-1000 Control System Controller: 6600-401 (Entire controller is changed instead of the circuit board)
Transformer:	N/A Entire controller is changed instead of the circuit board
Heater:	Heater: 5.5 kW 240 VAC Hi-Flow DSMT (Nuts and gaskets included) 6500-417
Panel:	Control Panel: LCD 1/3 VGA color graphics, 1-Pump 60 Hz (6600-099) Wireless RF remote control with LCD display (6560-304); Harness: Topside control panel to main load box (6560-956)
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-363) Universal mounting bracket kit (6000-535)
Temp Sensor:	Temperature Sensor with DSMT connector cable, resistance can be checked 6600-181
Hi-Limit:	Hi-Limit Sensor with DSMT connector cable, resistance can be checked 6600-179
Flow Switch:	Flow switch assembly with DSMT connector cable 6560-651
Circulation Pump:	Pump: Circmaster 230V 60HZ 48F 6500-907
21 Total Jets:	2-NX2 (6540-815), 5-RX3 (6541-288), 9-FX (20285-001), 4-FX Rotational (6541-031), 1-FX Large Rotational (6541-132)
Air Controls:	2-Knob (20101-001), 2-Body and stem (6540-377)
Diverter:	1-(3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	1-75 ft ² (6540-164J), 1-40 ft ² (6473-157J), 1-Spun bound (6473-161J) Debris attachment bag: 6570-398

Year:	2014
Model:	J-LXL
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	L-LX
Board:	J-LX Series LED circuit board Board: 6600-726 Micro Chip: 6660-285 Rev. 3.61
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-LX LED SMT 2-Pump with cable to DCU (MiniDin) 6600-506
Pump #1:	2.5 HP 2-SP 240V NB 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
38 Total Stainless Steel Jets (Standard):	2-MX2 (2540-367, 6541-133), 6-NX2 (6540-815), 4-RX2 (6541-288), 23-FX (20285-001), 3-FX Large Rotational (6541-132)
Air Controls:	3 - on/off air toggle control (6541-142)
Diverter:	1 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-75 ft ² (6540-164J), 1-Skimmer Weir Filter (6540-188) Debris attachment bag: 6570-392

Year:	2014
Model:	J-LX
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	L-LX
Board:	J-LX Series LED circuit board Board: 6600-726 Micro Chip: 6660-285 Rev. 3.61
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-LX SMT LED 2-Pump with cable to DCU (MiniDin) 6600-506
Pump #1:	2.5 HP 2-SP 240V NB 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
36 Total Stainless Steel Jets (Standard):	2-MX2 (2540-367, 6541-133), 4-NX2 (6540-815), 4-RX2 (6541-288), 21-FX (20285-001), 5-FX Large Rotational (6541-132)
Air Controls:	4 - on/off air toggle control (6541-142)
Diverter:	1 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-75 ft ² (6540-164J), 1-Skimmer Weir Filter (6540-188) Debris attachment bag: 6570-392

Year:	2014
Model:	J-385
Size:	91" x 91" x 38" (231 cm x 231 cm x 96.5 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-293 Micro Chip: 6660-289 Rev. 3.82
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-300 LED 2-Pump with cable to DCU (MiniDin) 6600-175
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
49 Total Stainless Steel Jets (Standard):	3-MX2 (2540-367, 6541-133), 2-BX (6541-231), 4-NX2 (6540-815), 17-FX (20285-001), 8-FX Small (6541-117), 7-FX Rotational (6541-031), 4-FX Large (6541-118), 4-FX Large Rotational (6541-132)
Air Controls:	4 - on/off air toggle control (6541-142)
Diverter:	2 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

Year:	2014
Model:	J-375
Size:	91" x 91" x 38" (231 cm x 231 cm x 96.5 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-293 Micro Chip: 6660-289 Rev. 3.82
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-300 LED 2-Pump with cable to DCU (MiniDin) 6600-175
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
50 Total Stainless Steel Jets (Standard):	5-MX2 (2540-367, 6541-133), 12-BX (6541-231), 4-NX2 (6540-815), 18-FX (20285-001), 6-FX Rotational (6541-031), 2-FX Large (6541-118), 3-FX Large Rotational (6541-132)
Air Controls:	4 - on/off air toggle control (6541-142)
Diverter:	2 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

Year:	2014
Model:	J-365
Size:	91" x 84" x 38" (231 cm x 213.5 cm x 96.5 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-293 Micro Chip: 6660-289 Rev. 3.82
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-300 SMT LED 2-Pump with cable to DCU (MiniDin) 6600-175
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
44 Total Stainless Steel Jets (Standard):	3-MX2 (2540-367, 6541-133), 4-NX2 (6540-815), 19-FX (20285-001), 8-FX Small (6541-117), 4-FX Rotational, 3-FX Large (6541-118), 3-FX Large Rotational (6541-132)
Air Controls:	4 - on/off air toggle control (6541-142)
Diverter:	2 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

Year:	2014
Model:	J-355
Size:	91" x 84" x 38" (231 cm x 213.5 cm x 96.5 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-293 Micro Chip: 6660-289 Rev. 3.82
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-300 LED 2-Pump with cable to DCU (MiniDin) 2600-328
Pump #1:	2.5 HP 2-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
42 Total Stainless Steel Jets (Standard):	5-MX2 (2540-367, 6541-133), 12-BX (6541-231), 2-NX2 (6540-815), 14-FX (20285-001), 4-FX Rotational (6541-031), 2-FX Large (6541-118), 3-FX Large Rotational (6541-132)
Air Controls:	3 - on/off air toggle control (6541-142)
Diverter:	2 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

Year:	2014
Model:	J-345
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-293 Micro Chip: 6660-289 Rev. 3.82
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-300 SMT LED 2-Pump with cable to DCU (MiniDin) 6600-175
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
39 Total Stainless Steel Jets (Standard):	3-MX2 (2540-367, 6541-133), 19-FX (20285-001), 8-FX Small (6541-117), 4-FX Rotational (6541-031), 2-FX Large (6541-118), 3-FX Large Rotational (6541-132)
Air Controls:	4 - on/off air toggle control (6541-142)
Diverter:	2 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

Year:	2014
Model:	J-335
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-293 Micro Chip: 6660-289 Rev. 3.82
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-300 SMT LED 2-Pump with cable to DCU (MiniDin) 6600-175
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
40 Total Stainless Steel Jets (Standard)*:	2-MX2 (2540-367, 6541-133), 12-BX (6541-231), 16-FX (20285-001), 4-FX Rotational (6541-031), 2-FX Large (6541-118), 4-FX Large Rotational (6541-132)
Air Controls:	3 - on/off air toggle control (6541-142)
Diverter:	2 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

Year:	2014
Model:	J-325
Size:	76" x 84" x 34" (193 cm x 213.5 cm x 86.5 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-295 Micro Chip: 6660-289 Rev. 3.82
Transformer:	120V 12V 6560-274 (without plug) 6000-516 (with plug)
Heater:	Heater: 1.0 kW 120V/4.4kW 240 VAC tube heater (convertible) 6500-063 (1-Adapter (6540-034))
Panel:	J-300 SMT LED 1-Pump with cable to DCU (MiniDin) 6600-713
Pump #1:	1.5 HP 2-SP 120V 48F pump (6500-345) Universal mounting bracket kit (6000-532)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with tee fitting 6560-852 (2x 6540-262 adapters)
Circulation Pump:	Pump: Circ E-10 115V 60 Hz 6500-460
21 Total Stainless Steel Jets (Standard):	6-FX (20285-001), 4-FX Small (6541-117), 2-FX Rotational (6541-031), 2-FX Large (6541-118), 7-FX Large Rotational (6541-132)
Air Controls:	4 - on/off air toggle control (6541-142)
Diverter:	1 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

Year:	2014
Model:	J-315
Size:	76" x 66" x 32" (193 cm x 168 cm x 81 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-295 Micro Chip: 6660-289 Rev. 3.82
Transformer:	120V 12V 6560-274 (without plug) 6000-516 (with plug)
Heater:	Heater: 1.0 kW 120V/4.4kW 240 VAC tube heater (convertible) 6500-063 (1-Adapter (6540-034)
Panel:	J-300 SMT LED 1-Pump with cable to DCU (MiniDin) 6600-713
Pump #1:	1.5 HP 2-SP 120V 48F pump (6500-345) Universal mounting bracket kit (6000-532)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with tee fitting 6560-852 (2x 6540-262 adapters)
Circulation Pump:	Pump: Circ E-10 115V 60 Hz 6500-460
21 Total Stainless Steel Jets (Standard):	6-BX (6541-231), 8-FX (20285-001), 2-FX Rotational (6541-031), 5-FX Large Rotational (6541-132)
Air Controls:	3 - on/off air toggle control (6541-142)
Diverter:	1 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

Year:	2014
Model:	J-280
Size:	90" x 90" x 36.5" (228.6 cm x 228.6 cm x 92.7 cm)
Series:	J-200
Board:	J-200 Series LED circuit board Board: 6600-720 Micro Chip: 6660-287 Rev. 5.60
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5kW 240 VAC 6000-156
Panel:	J-200 SMT LED 2-Pump 6600-501
Pump #1:	2.5 HP 2-SP 240V 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Pressure Switch 6560-869
44 Total Stainless Steel Jets (Standard):	8-Classic Direct (2540-265), 16-Classic Euro (2540-255), 7-Classic Luxury (2540-433), 6-Classic Mini (2540-319), 6-Classic Rotational (2472-610), 1-Classic Whirl (2540-529)
Air Controls:	4 - Knob (2540-281), Manifold (6541-284), Nut (6541-282), Gasket (6541-283)
Diverter:	1 - Knob (6540-274), Cap (2540-273), Stem o-ring (2x 6541-241), Body o-ring (6541-240), Gate (6541-242)
Filter:	1-95 ft ² (2540-381J) Debris attachment bag: 6570-392

Year:	2014
Model:	J-275
Size:	90" x 90" x 36.5" (228.6 cm x 228.6 cm x 92.7 cm)
Series:	J-200
Board:	J-200 Series LED circuit board Board: 6600-720 Micro Chip: 6660-287 Rev. 5.60
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5kW 240 VAC 6000-156
Panel:	J-200 SMT LED 2-Pump 6600-501
Pump #1:	2.5 HP 2-SP 240V 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Pressure Switch 6560-869
45 Total Stainless Steel Jets (Standard):	8-Classic Direct (2540-265), 14-Classic Euro (2540-255), 6-Classic Luxury (2540-433), 3-Classic Mini (2540-319), 6-Classic Pulsator (2540-245), 6-Classic Rotational (2472-610), 2-Classic Turbo (6541-652)
Air Controls:	3 - Knob (2540-281), Manifold (6541-284), Nut (6541-282), Gasket (6541-283)
Filter:	1-50 ft ² (373045)

Year:	2014
Model:	J-245
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	J-200
Board:	J-200 Series LED circuit board Board: 6600-720 Micro Chip: 6660-287 Rev. 5.60
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5kW 240 VAC 6000-156
Panel:	J-200 SMT LED 2-Pump 6600-501
Pump #1:	2.5 HP 2-SP 240V 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Pressure Switch 6560-869
35 Total Stainless Steel Jets (Standard):	4-Classic Direct (2540-265), 18-Classic Euro (2540-255), 5-Classic Luxury (2540-433), 2-Classic Mini (2540-319), 4-Classic Rotational (2472-610), 2-Classic Turbo (6541-652)
Air Controls:	3 - Knob (2540-281), Manifold (6541-284), Nut (6541-282), Gasket (6541-283)
Filter:	1-50 ft ² (373045)

Year:	2014
Model:	J-235
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	J-200
Board:	J-200 Series LED circuit board Board: 6600-720 Micro Chip: 6660-287 Rev. 5.60
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5kW 240 VAC 6000-156
Panel:	J-200 SMT LED 2-Pump 6600-501
Pump #1:	2.5 HP 2-SP 240V 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Pressure Switch 6560-869
35 Total Stainless Steel Jets (Standard):	4-Classic Direct (2540-265), 12-Classic Euro (2540-255), 6-Classic Luxury (2540-433), 3-Classic Mini (2540-319), 4-Classic Pulsator (2540-245), 4-Classic Rotational (2472-610), 2-Classic Turbo (6541-652)
Air Controls:	3 - Knob (2540-281), Manifold (6541-284), Nut (6541-282), Gasket (6541-283)
Filter:	1-50 ft ² (373045)

Year:	2014
Model:	J-210
Size:	78" Round x 36" (198 cm Round x 91.5 cm)
Series:	J-200
Board:	J-200 Series LED circuit board Board: 6600-722 Micro Chip: 6660-287 Rev. 5.60
Transformer:	240V 12V 6560-274 (without plug) 6000-516 (with plug)
Heater:	Heater: 1kW 120 VAC/4kW 240V (convertible) 6000-338
Panel:	J-200 SMT LED 1-Pump 6600-500
Pump #1:	1.5 HP 2-SP 120V 48F pump (6500-345) Universal mounting bracket kit (6000-532)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Pressure Switch 6560-869
19 Total Textured Jets (Standard):	4-Classic Direct (2540-261), 4-Classic Luxury (2540-431), 10-Classic Mini (2540-317), 1-Divert-A-Jet (6541-800)
Air Controls:	3 - Knob (2540-281), Manifold (6541-284), Nut (6541-282), Gasket (6541-283)
Filter:	1-50 ft ² (373045)

Year:	2013
Model:	J-495
Size:	90" x 110" x 41" Front/46" Back (228.6 cm x 279.4 cm x 104.14 cm Front/116 cm Back)
Series:	J-400
Board:	J-1000 Control System Controller: 6600-400 (Entire controller is changed insted of the circuit board)
Transformer:	N/A Entire controller is changed insted of the circuit board
Heater:	Heater: 5.5 kW 240 VAC Hi-Flow DSMT (Nuts and gaskets included) 6500-417
Panel:	Control Panel: LCD 1/3 VGA color graphics, 3-Pump 60 Hz (6600-099) Wireless RF remote control with LCD display (6560-304); Harness: Topside control panel to main load box (6560-956)
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #3:	2.5 HP 1-SP 240V NB 56F pump (6500-363) Universal mounting bracket kit (6000-535)
Temp Sensor:	Temperature Sensor with DSMT connector cable, resistance can be checked 6600-181
Hi-Limit:	Hi-Limit Sensor with DSMT connector cable, resistance can be checked 6600-179
Flow Switch:	Flow switch assembly with DSMT connector cable 6560-651
Circulation Pump:	Pump: Circmaster 230V 60HZ 48F 6500-907
62 Total Jets*:	3-MX3 (2540-367, 6541-133), 18-NX2 (6540-815), 11-RX2 (20093-001), 24-FX (20285-001), 5-FX2-S (6541-568), 1-IX (20094-001)
Air Controls:	5-Knob (20101-001), 5-Body and stem (6540-377)
Diverter:	2 (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	1-75 ft ² (6540-164J), 1-40 ft ² (6473-157J), 1-Spun bound (6473-161J) Debris attachment bag: 6570-398

*2013 two styles of jets were used for the MX, FX2-S, RX and PX

Year:	2013
Model:	J-480
Size:	94" x 94" x 39" Front/44" Back (239 cm x 239 cm x 99 cm Front/112 cm Back)
Series:	J-400
Board:	J-1000 Control System Controller: 6600-401 (Entire controller is changed insted of the circuit board)
Transformer:	N/A Entire controller is changed insted of the circuit board
Heater:	Heater: 5.5 kW 240 VAC Hi-Flow DSMT (Nuts and gaskets included) 6500-417
Panel:	Control Panel: LCD 1/3 VGA color graphics, 2-Pump 60 Hz (6600-099) Wireless RF remote control with LCD display (6560-304); Harness: Topside control panel to main load box (6560-956)
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-365) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Temperature Sensor with DSMT connector cable, resistance can be checked 6600-181
Hi-Limit:	Hi-Limit Sensor with DSMT connector cable, resistance can be checked 6600-179
Flow Switch:	Flow switch assembly with DSMT connector cable 6560-651
Circulation Pump:	Pump: Circmaster 230V 60HZ 48F 6500-907
48 Total Jets*:	3-MX3 (2540-367, 6541-133), 4-NX2 (6540-815), 6-PX (6541-561, 6541-562, 6541-287, 6540-330), 6-RX2 (20093-001), 22-FX (20285-001), 6-FX2-S (6541-568), 1-IX (6560-103)
Air Controls:	4-Knob (20101-001), 4-Body and stem (6540-377)
Diverter:	2 (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	1-75 ft ² (6540-164J), 1-40 ft ² (6473-157J), 1-Spun bound (6473-161J) Debris attachment bag: 6570-398

*2013 two styles of jets were used for the MX, FX2-S, RX and PX

Year:	2013
Model:	J-470
Size:	91" x 91" x 39" Front/44" Back (231 cm x 231 cm x 99 cm Front/112 cm Back)
Series:	J-400
Board:	J-1000 Control System Controller: 6600-401 (Entire controller is changed insted of the circuit board)
Transformer:	N/A Entire controller is changed insted of the circuit board
Heater:	Heater: 5.5 kW 240 VAC Hi-Flow DSMT (Nuts and gaskets included) 6500-417
Panel:	Control Panel: LCD 1/3 VGA color graphics, 2-Pump 60 Hz (6600-099) Wireless RF remote control with LCD display (6560-304); Harness: Topside control panel to main load box (6560-956)
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-365) Universal mounting bracket kit (6000-535)
Temp Sensor:	Temperature Sensor with DSMT connector cable, resistance can be checked 6600-181
Hi-Limit:	Hi-Limit Sensor with DSMT connector cable, resistance can be checked 6600-179
Flow Switch:	Flow switch assembly with DSMT connector cable 6560-651
Circulation Pump:	Pump: Circmaster 230V 60HZ 48F 6500-907
39 Total Jets*:	3-MX3 (2540-367, 6541-133), 4-NX2 (6540-815), 6-RX2 (20093-001), 20-FX (20285-001), 5-FX2-S (6541-568), 1-IX (6560-103)
Air Controls:	4-Knob (20101-001), 4-Body and stem (6540-377)
Diverter:	2 (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	1-75 ft ² (6540-164J), 1-40 ft ² (6473-157J), 1-Spun bound (6473-161J) Debris attachment bag: 6570-398

*2013 two styles of jets were used for the MX, FX2-S, RX and PX

Year:	2013
Model:	J-465
Size:	88" x 88" x 39" Front/43" Back (223.5 cm x 223.5 cm x 99 cm Front/109 cm Back)
Series:	J-400
Board:	J-1000 Control System Controller: 6600-401 (Entire controller is changed insted of the circuit board)
Transformer:	N/A Entire controller is changed insted of the circuit board
Heater:	Heater: 5.5 kW 240 VAC Hi-Flow DSMT (Nuts and gaskets included) 6500-417
Panel:	Control Panel: LCD 1/3 VGA color graphics, 2-Pump 60 Hz (6600-099) Wireless RF remote control with LCD display (6560-304); Harness: Topside control panel to main load box (6560-956)
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-365) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Temperature Sensor with DSMT connector cable, resistance can be checked 6600-181
Hi-Limit:	Hi-Limit Sensor with DSMT connector cable, resistance can be checked 6600-179
Flow Switch:	Flow switch assembly with DSMT connector cable 6560-651
Circulation Pump:	Pump: Circmaster 230V 60HZ 48F 6500-907
39 Total Jets*:	5-MX3 (2540-367, 6541-133), 4-NX2 (6540-815), 4-PX (6541-512), 6-RX2 (20093-001), 12-FX (20285-001), 7-FX2-S (6541-568), 1-IX (6560-103)
Air Controls:	3-Knob (20101-001), 3-Body and stem (6540-377)
Diverter:	2-(3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	1-75 ft ² (6540-164J), 1-40 ft ² (6473-157J), 1-Spun bound (6473-161J) Debris attachment bag: 6570-398

*2013 two styles of jets were used for the MX, FX2-S, RX and PX

Year:	2013
Model:	J-425
Size:	76" x 87" x 34" Front/39" Back (193.04 cm x 220.08 cm x 86.36 cm Front/99.06 cm Back)
Series:	J-400
Board:	J-1000 Control System Controller: 6600-401 (Entire controller is changed insted of the circuit board)
Transformer:	N/A Entire controller is changed insted of the circuit board
Heater:	Heater: 5.5 kW 240 VAC Hi-Flow DSMT (Nuts and gaskets included) 6500-417
Panel:	Control Panel: LCD 1/3 VGA color graphics, 2-Pump 60 Hz (6600-099) Wireless RF remote control with LCD display (6560-304); Harness: Topside control panel to main load box (6560-956)
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Temperature Sensor with DSMT connector cable, resistance can be checked 6600-181
Hi-Limit:	Hi-Limit Sensor with DSMT connector cable, resistance can be checked 6600-179
Flow Switch:	Flow switch assembly with DSMT connector cable 6560-651
Circulation Pump:	Pump: Circmaster 230V 60HZ 48F 6500-907
27 Total Jets*:	3-MX3 (2540-367, 6541-133), 2-NX2 (6540-815), 2-RX2 (20093-001), 14-FX (20285-001), 5-FX2-S (6541-568), 1-IX (6560-103)
Air Controls:	4-Knob (20101-001), 4-Body and stem (6540-377)
Diverter:	1-(3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	1-75 ft ² (6540-164J), 1-40 ft ² (6473-157J), 1-Spun bound (6473-161J) Debris attachment bag: 6570-398

*2013 two styles of jets were used for the MX, FX2-S, RX and PX

Year:	2013
Model:	J-415
Size:	76" x 66" x 32" (193.04 cm x 167.64 cm x 81.28 cm)
Series:	J-400
Board:	J-1000 Control System Controller: 6600-401 (Entire controller is changed insted of the circuit board)
Transformer:	N/A Entire controller is changed insted of the circuit board
Heater:	Heater: 5.5 kW 240 VAC Hi-Flow DSMT (Nuts and gaskets included) 6500-417
Panel:	Control Panel: LCD 1/3 VGA color graphics, 1-Pump 60 Hz (6600-099) Wireless RF remote control with LCD display (6560-304); Harness: Topside control panel to main load box (6560-956)
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-363) Universal mounting bracket kit (6000-535)
Temp Sensor:	Temperature Sensor with DSMT connector cable, resistance can be checked 6600-181
Hi-Limit:	Hi-Limit Sensor with DSMT connector cable, resistance can be checked 6600-179
Flow Switch:	Flow switch assembly with DSMT connector cable 6560-651
Circulation Pump*:	Pump: Circmaster 230V 60HZ 48F 6500-907
21 Total Jets**:	2-NX2 (6540-815), 5-RX2 (20093-001), 13-FX (20285-001), 1-FX2-S (6541-568)
Air Controls:	2-Knob (20101-001), 2-Body and stem (6540-377)
Diverter:	1-(3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	1-75 ft ² (6540-164J), 1-40 ft ² (6473-157J), 1-Spun bound (6473-161J) Debris attachment bag: 6570-398

*Circulation Pump can be either the 6500-907 or 6500-913

**2013 two styles of jets were used for the MX, FX2-S, RX and PX

Year:	2013
Model:	J-LXL
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	L-LX
Board:	J-LX Series LED circuit board Board: 6600-726 Micro Chip: 6660-285 Rev. 3.61
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-LX LED SMT 2-Pump with cable to DCU (MiniDin) 6600-506
Pump #1:	2.5 HP 2-SP 240V NB 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
38 Total Stainless Steel Jets (Standard)*:	2-MX2 (6541-056, 6541-192), 6-NX2 (6540-815), 4-RX2 (20093-001), 23-FX (20285001), 3-FX2-S (6541-181)
Air Controls:	3 - on/off air toggle control (6541-142)
Diverter:	1 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-75 ft ² (6540-164J), 1-Skimmer Weir Filter (6540-188) Debris attachment bag: 6570-392

*2013 two styles of jets were used for the MX, RX and FX2-S

Year:	2013
Model:	J-LX
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	L-LX
Board:	J-LX Series LED circuit board Board: 6600-726 Micro Chip: 6660-285 Rev. 3.61
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-LX SMT LED 2-Pump with cable to DCU (MiniDin) 6600-506
Pump #1:	2.5 HP 2-SP 240V NB 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
36 Total Stainless Steel Jets (Standard)*:	2-MX2 (6541-056, 6541-192), 4-NX2 (6540-815), 4-RX2 (20093-001), 21-FX (20285001), 5-FX2-S (6541-181)
Air Controls:	4 - on/off air toggle control (6541-142)
Diverter:	1 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-75 ft ² (6540-164J), 1-Skimmer Weir Filter (6540-188) Debris attachment bag: 6570-392

*2013 two styles of jets were used for the MX, RX and FX2-S

Year:	2013
Model:	J-375
Size:	91" x 91" x 38" (231 cm x 231 cm x 96.5 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-726 Micro Chip: 6660-285 Rev. 3.61
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-300 SMT LED 2-Pump with cable to DCU (MiniDin) 6600-504
Pump #1:	2.5 HP 2-SP 240V NB 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
46 Total Stainless Steel Jets (Standard)*:	5-MX2 (6541-056, 6541-192), 12-BX (6541-231), 4-NX2 (6540-815), 21-FX (20285-001), 4-FX2-S (6541-568)
Air Controls:	4 - on/off air toggle control (6541-142)
Diverter:	2 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

*2013 two styles of jets were used for the MX and FX2-S

Year:	2013
Model:	J-365
Size:	91" x 84" x 38" (231 cm x 213.5 cm x 96.5 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-726 Micro Chip: 6660-285 Rev. 3.61
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-300 SMT LED 2-Pump with cable to DCU (MiniDin) 6600-504
Pump #1:	2.5 HP 2-SP 240V NB 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
32 Total Stainless Steel Jets (Standard*):	3-MX2 (6541-056, 654-192), 23-FX (20285-001), 6-FX2-S (6541-568)
Air Controls:	5 - on/off air toggle control (6541-142)
Diverter:	2 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

*2013 two styles of jets were used for the MX and FX2-S

Year:	2013
Model:	J-355
Size:	91" x 84" x 38" (231 cm x 213.5 cm x 96.5 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-726 Micro Chip: 6660-285 Rev. 3.61
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-300 LED 2-Pump with cable to DCU (MiniDin) 2600-328
Pump #1:	2.5 HP 2-SP 240V NB 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
40 Total Stainless Steel Jets (Standard)*:	5-MX2 (6541-056, 6541-192), 12-BX (6541-231), 19-FX (20285-001), 4-FX2-S (6541-568)
Air Controls:	4 - on/off air toggle control (6541-142)
Diverter:	2 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

*2013 two styles of jets were used for the MX and FX2-S

Year:	2013
Model:	J-345
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-726 Micro Chip: 6660-285 Rev. 3.61
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-300 SMT LED 2-Pump with cable to DCU (MiniDin) 6600-504
Pump #1:	2.5 HP 2-SP 240V NB 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-365) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
27 Total Stainless Steel Jets (Standard)*:	5-MX2 (6541-056, 6541-192), 18-FX (20285-001), 4-FX2-S (6541-568)
Air Controls:	4 - on/off air toggle control (6541-142)
Diverter:	2 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

*2013 two styles of jets were used for the MX and FX2-S

Year:	2013
Model:	J-335
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-726 Micro Chip: 6660-285 Rev. 3.61
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-300 SMT LED 2-Pump with cable to DCU (MiniDin) 6600-504
Pump #1:	2.5 HP 2-SP 240V NB 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
36 Total Stainless Steel Jets (Standard)*:	2-MX2 (6541-056, 6541-192), 12-BX (6541-231), 18-FX (20285-001), 4-FX2-S (6541-568)
Air Controls:	3 - on/off air toggle control (6541-142)
Diverter:	1 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

*2013 two styles of jets were used for the MX and FX2-S

Year:	2013
Model:	J-325
Size:	76" x 84" x 34" (193 cm x 213.5 cm x 86.5 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-044 Micro Chip: 6660-285 Rev. 3.61
Transformer:	120V 12V 6560-274 (without plug) 6000-516 (with plug)
Heater:	Heater: 1.0 kW 120V/4.4kW 240 VAC tube heater (convertible) 6500-063 (1-Adapter (6540-034)
Panel:	J-300 SMT LED 1-Pump with cable to DCU (MiniDin) 6600-503
Pump #1:	1.5 HP 2-SP 120V 48F pump (6500-345) Universal mounting bracket kit (6000-532)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with tee fitting 6560-852 (2x 6540-262 adapters)
Circulation Pump:	Pump: Circ E-10 115V 60 Hz 6500-460
15 Total Stainless Steel Jets (Standard)*:	4-FX (20285-001), 11-FX2-S (6541-568)
Air Controls:	3 - on/off air toggle control (6541-142)
Diverter:	1 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

*2013 two styles of jets were used for the FX2-S jets

Year:	2013
Model:	J-315
Size:	76" x 66" x 32" (193 cm x 168 cm x 81 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-044 Micro Chip: 6660-285 Rev. 3.61
Transformer:	120V 12V 6560-274 (without plug) 6000-516 (with plug)
Heater:	Heater: 1.0 kW 120V/4.4kW 240 VAC tube heater (convertible) 6500-063 (1-Adapter (6540-034)
Panel:	J-300 SMT LED 1-Pump with cable to DCU (MiniDin) 6600-503
Pump #1:	1.5 HP 2-SP 120V 48F pump (6500-345) Universal mounting bracket kit (6000-532)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with tee fitting 6560-852 (2x 6540-262 adapters)
Circulation Pump:	Pump: Circ E-10 115V 60 Hz 6500-460
13 Total Stainless Steel Jets (Standard)*:	6-FX (20285-001), 7-FX2-S (6541-568)
Air Controls:	2 - on/off air toggle control (6541-142)
Diverter:	1 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

*2013 two styles of jets were used for the FX2-S jets

Year:	2013
Model:	J-280
Size:	90" x 90" x 36.5" (228.6 cm x 228.6 cm x 92.7 cm)
Series:	J-200
Board:	J-200 Series LED circuit board Board: 6600-720 Micro Chip: 6660-287 Rev. 5.60
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5kW 240 VAC 6000-156
Panel:	J-200 SMT LED 2-Pump 6600-501
Pump #1:	2.5 HP 2-SP 240V 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Pressure Switch 6560-869
44 Total Stainless Steel Jets (Standard):	8-Classic Direct (2540-265), 16-Classic Euro (2540-255), 13-Classic Luxury (2540-433), 6-Classic Mini (2540-319), 1-Classic Whirl (2540-529)
Air Controls:	4 - Knob (2540-281), Manifold (6541-284), Nut (6541-282), Gasket (6541-283)
Diverter:	1 - Knob (6540-274), Cap (2540-273), Stem o-ring (2x 6541-241), Body o-ring (6541-240), Gate (6541-242)
Filter:	1-95 ft ² (2540-381J) Debris attachment bag: 6570-392

Year:	2013
Model:	J-275
Size:	90" x 90" x 36.5" (228.6 cm x 228.6 cm x 92.7 cm)
Series:	J-200
Board:	J-200 Series LED circuit board Board: 6600-720 Micro Chip: 6660-287 Rev. 5.60
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5kW 240 VAC 6000-156
Panel:	J-200 SMT LED 2-Pump 6600-501
Pump #1:	2.5 HP 2-SP 240V 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Pressure Switch 6560-869
45 Total Stainless Steel Jets (Standard):	8-Classic Direct (2540-265), 14-Classic Euro (2540-255), 12-Classic Luxury (2540-433), 3-Classic Mini (2540-319), 6-Classic Pulsator (2540-245), 2-Classic Turbo (6541-652)
Air Controls:	3 - Knob (2540-281), Manifold (6541-284), Nut (6541-282), Gasket (6541-283)
Filter:	1-50 ft ² (373045)

Year:	2013
Model:	J-245
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	J-200
Board:	J-200 Series LED circuit board Board: 6600-720 Micro Chip: 6660-287 Rev. 5.60
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5kW 240 VAC 6000-156
Panel:	J-200 SMT LED 2-Pump 6600-501
Pump #1:	2.5 HP 2-SP 240V 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Pressure Switch 6560-869
35 Total Stainless Steel Jets (Standard):	4-Classic Direct (2540-265), 18-Classic Euro (2540-255), 9-Classic Luxury (2540-433), 2-Classic Mini (2540-319), 2-Classic Turbo (6541-652)
Air Controls:	3 - Knob (2540-281), Manifold (6541-284), Nut (6541-282), Gasket (6541-283)
Filter:	1-50 ft ² (373045)

Year:	2013
Model:	J-235
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	J-200
Board:	J-200 Series LED circuit board Board: 6600-720 Micro Chip: 6660-287 Rev. 5.60
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5kW 240 VAC 6000-156
Panel:	J-200 SMT LED 2-Pump 6600-501
Pump #1:	2.5 HP 2-SP 240V 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Pressure Switch 6560-869
35 Total Stainless Steel Jets (Standard):	4-Classic Direct (2540-265), 12-Classic Euro (2540-255), 10-Classic Luxury (2540-433), 3-Classic Mini (2540-319), 4-Classic Pulsator (2540-245), 2-Classic Turbo (6541-652)
Air Controls:	3 - Knob (2540-281), Manifold (6541-284), Nut (6541-282), Gasket (6541-283)
Filter:	1-50 ft ² (373045)

Year:	2013
Model:	J-210
Size:	78" Round x 36" (198 cm Round x 91.5 cm)
Series:	J-200
Board:	J-200 Series LED circuit board Board: 6600-722 Micro Chip: 6660-287 Rev. 5.60
Transformer:	240V 12V 6560-274 (without plug) 6000-516 (with plug)
Heater:	Heater: 1kW 120 VAC/4kW 240V (convertible) 6000-338
Panel:	J-200 SMT LED 1-Pump 6600-500
Pump #1:	1.5 HP 2-SP 120V 48F pump (6500-345) Universal mounting bracket kit (6000-532)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Pressure Switch 6560-869
19 Total Textured Jets (Standard):	4-Classic Direct (2540-261), 4-Classic Luxury (2540-431), 10-Classic Mini (2540-317), 1-Divert-A-Jet (6541-800)
Air Controls:	3 - Knob (2540-281), Manifold (6541-284), Nut (6541-282), Gasket (6541-283)
Filter:	1-50 ft ² (373045)

Year:	2012
Model:	J-495
Size:	90" x 110" x 41" Front/46" Back (228.6 cm x 279.4 cm x 104.14 cm Front/116 cm Back)
Series:	J-400
Board:	J-1000 Control System Controller: 6600-400 (Entire controller is changed insted of the circuit board)
Transformer:	N/A Entire controller is changed insted of the circuit board
Heater:	Heater: 5.5 kW 240 VAC Hi-Flow DSMT (Nuts and gaskets included) 6500-417
Panel:	Control Panel: LCD 1/3 VGA color graphics, 3-Pump 60 Hz (6600-405) Wireless RF remote control with LCD display (6560-336); Harness: Topside control panel to main load box (6560-956)
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #3:	2.5 HP 1-SP 240V NB 56F pump (6500-363) Universal mounting bracket kit (6000-535)
Temp Sensor:	Temperature Sensor with DSMT connector cable, resistance can be checked 6600-181
Hi-Limit:	Hi-Limit Sensor with DSMT connector cable, resistance can be checked 6600-179
Flow Switch:	Flow switch assembly with DSMT connector cable 6560-651
Circulation Pump:	Pump: Circmaster 230V 60HZ 48F 6500-907
62 Total Jets:	3-MX2 (6541-056, 6541-192), 18-NX2 (6540-815), 11-RX2 (20093-001), 24-FX (20285-001), 5-FX2-S (6541-568), 1-IX (20094-001)
Air Controls:	5-Knob (20101-001), 5-Body and stem (6540-377)
Diverter:	2 (3-way diverter) - Knob (2540-533), Cap (6540-729), stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	1-75 ft ² (6540-164J), 1-40 ft ² (6473-157J), 1-Spun bound (6473-161J) Debris attachment bag: 6570-398

Year:	2012
Model:	J-480
Size:	94" x 94" x 39" Front/44" Back (239 cm x 239 cm x 99 cm Front/112 cm Back)
Series:	J-400
Board:	J-1000 Control System Controller: 6600-401 (Entire controller is changed insted of the circuit board)
Transformer:	N/A Entire controller is changed insted of the circuit board
Heater:	Heater: 5.5 kW 240 VAC Hi-Flow DSMT (Nuts and gaskets included) 6500-417
Panel:	Control Panel: LCD 1/3 VGA color graphics, 2-Pump 60 Hz (6600-405) Wireless RF remote control with LCD display (6560-336); Harness: Topside control panel to main load box (6560-956)
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-365) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Temperature Sensor with DSMT connector cable, resistance can be checked 6600-181
Hi-Limit:	Hi-Limit Sensor with DSMT connector cable, resistance can be checked 6600-179
Flow Switch:	Flow switch assembly with DSMT connector cable 6560-651
Circulation Pump:	Pump: Circmaster 230V 60HZ 48F 6500-907
48 Total Jets:	3-MX2 (6541-056, 6541-192), 4-NX2 (6540-815), 6-RX2 (20093-001), 6-PX (6541-512) 22-FX (20285-001), 6-FX2-S (6541-181), 1-IX (20094-001)
Air Controls:	4-Knob (20101-001), 4-Body and stem (6540-377)
Diverter:	2 (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	1-35 ft ² (2540-387J), 1-50 ft ² (6473-158), 1-Spun bound (6473-161J) Debris attachment bag: 2540-389

Year:	2012
Model:	J-470
Size:	91" x 91" x 39" Front/44" Back (231 cm x 231 cm x 99 cm Front/112 cm Back)
Series:	J-400
Board:	J-1000 Control System Controller: 6600-401 (Entire controller is changed insted of the circuit board)
Transformer:	N/A Entire controller is changed insted of the circuit board
Heater:	Heater: 5.5 kW 240 VAC Hi-Flow DSMT (Nuts and gaskets included) 6500-417
Panel:	Control Panel: LCD 1/3 VGA color graphics, 2-Pump 60 Hz (6600-405) Wireless RF remote control with LCD display (6560-336); Harness: Topside control panel to main load box (6560-956)
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-365) Universal mounting bracket kit (6000-535)
Temp Sensor:	Temperature Sensor with DSMT connector cable, resistance can be checked 6600-181
Hi-Limit:	Hi-Limit Sensor with DSMT connector cable, resistance can be checked 6600-179
Flow Switch:	Flow switch assembly with DSMT connector cable 6560-651
Circulation Pump:	Pump: Circmaster 230V 60HZ 48F 6500-907
39 Total Jets:	3-MX2 (6541-056, 6541-192), 4-NX2 (6540-815), 6-RX2 (20093-001), 20-FX (20285-001), 5-FX2-S (6541-181), 1-IX (20094-001)
Air Controls:	4-Knob (20101-001), 4-Body and stem (6540-377)
Diverter:	2 (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	1-35 ft ² (2540-387J), 1-50 ft ² (6473-158), 1-Spun bound (6473-161J) Debris attachment bag: 2540-389

Year:	2012
Model:	J-465
Size:	88" x 88" x 39" Front/43" Back (223.5 cm x 223.5 cm x 99 cm Front/109 cm Back)
Series:	J-400
Board:	J-1000 Control System Controller: 6600-401 (Entire controller is changed insted of the circuit board)
Transformer:	N/A Entire controller is changed insted of the circuit board
Heater:	Heater: 5.5 kW 240 VAC Hi-Flow DSMT (Nuts and gaskets included) 6500-417
Panel:	Control Panel: LCD 1/3 VGA color graphics, 2-Pump 60 Hz (6600-405) Wireless RF remote control with LCD display (6560-336); Harness: Topside control panel to main load box (6560-956)
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-365) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Temperature Sensor with DSMT connector cable, resistance can be checked 6600-181
Hi-Limit:	Hi-Limit Sensor with DSMT connector cable, resistance can be checked 6600-179
Flow Switch:	Flow switch assembly with DSMT connector cable 6560-651
Circulation Pump:	Pump: Circmaster 230V 60HZ 48F 6500-907
37 Total Jets:	5-MX2 (6541-056, 6541-192), 4-NX2 (6540-815), 4-PX (6541-512), 6-RX2 (20093-001), 10-FX (20285-001), 7-FX2-S (6541-181), 1-IX (20094-001)
Air Controls:	3-Knob (20101-001), 3-Body and stem (6540-377)
Diverter:	1-(3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	1-35 ft ² (2540-387J), 1-50 ft ² (6473-158), 1-Spun bound (6473-161J) Debris attachment bag: 2540-389

Year:	2012
Model:	J-460
Size:	89" x 77" x 34" (226 cm x 196 cm x 86.5 cm)
Series:	J-400
Board:	J-1000 Control System Controller: 6600-401 (Entire controller is changed insted of the circuit board)
Transformer:	N/A Entire controller is changed insted of the circuit board
Heater:	Heater: 5.5 kW 240 VAC Hi-Flow DSMT (Nuts and gaskets included) 6500-417
Panel:	Control Panel: LCD 1/3 VGA color graphics, 2-Pump 60 Hz (6600-405) Wireless RF remote control with LCD display (6560-336); Harness: Topside control panel to main load box (6560-956)
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-365) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-365) Universal mounting bracket kit (6000-535)
Temp Sensor:	Temperature Sensor with DSMT connector cable, resistance can be checked 6600-181
Hi-Limit:	Hi-Limit Sensor with DSMT connector cable, resistance can be checked 6600-179
Flow Switch:	Flow switch assembly with DSMT connector cable 6560-651
Circulation Pump:	Pump: Circmaster 230V 60HZ 48F 6500-907
33 Total Jets:	5-MX2 (6541-056, 6541-192), 4-PX (6541-512), 4-RX2 (20093-001), 14-FX (20285-001), 5-FX2-S (6541-181), 1-IX (20094-001)
Air Controls:	4-Knob (20101-001), 4-Body and stem (6540-377)
Diverter:	1 (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	1-25 ft ² (2540-384), 1-30 ft ² (6473-156), 1-Spun bound (6473-161J) Debris attachment bag: 2540-389

Year:	2012
Model:	J-425
Size:	76" x 87" x 34" Front/39" Back (193.04 cm x 220.08 cm x 86.36 cm Front/99.06 cm Back)
Series:	J-400
Board:	J-1000 Control System Controller: 6600-401 (Entire controller is changed insted of the circuit board)
Transformer:	N/A Entire controller is changed insted of the circuit board
Heater:	Heater: 5.5 kW 240 VAC Hi-Flow DSMT (Nuts and gaskets included) 6500-417
Panel:	Control Panel: LCD 1/3 VGA color graphics, 2-Pump 60 Hz (6600-405) Wireless RF remote control with LCD display (6560-336); Harness: Topside control panel to main load box (6560-956)
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Temperature Sensor with DSMT connector cable, resistance can be checked 6600-181
Hi-Limit:	Hi-Limit Sensor with DSMT connector cable, resistance can be checked 6600-179
Flow Switch:	Flow switch assembly with DSMT connector cable 6560-651
Circulation Pump:	Pump: Circmaster 230V 60HZ 48F 6500-907
27 Total Jets:	3-MX2 (6541-056, 6541-192), 2-NX2 (6540-815), 2-RX2 (20093-001), 14-FX (20285-001), 5-FX2-S (6541-181), 1-IX (20094-001)
Air Controls:	4-Knob (20101-001), 4-Body and stem (6540-377)
Diverter:	1-(3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	1-75 ft ² (6540-164J), 1-40 ft ² (6473-157J), 1-Spun bound (6473-161J) Debris attachment bag: 6570-398

Year:	2012
Model:	J-415
Size:	76" x 66" x 32" (193.04 cm x 167.64 cm x 81.28 cm)
Series:	J-400
Board:	J-1000 Control System Controller: 6600-401 (Entire controller is changed insted of the circuit board)
Transformer:	N/A Entire controller is changed insted of the circuit board
Heater:	Heater: 5.5 kW 240 VAC Hi-Flow DSMT (Nuts and gaskets included) 6500-417
Panel:	Control Panel: LCD 1/3 VGA color graphics, 1-Pump 60 Hz (6600-405) Wireless RF remote control with LCD display (6560-336); Harness: Topside control panel to main load box (6560-956)
Pump #1:	2.5 HP 1-SP 240V NB 56F pump (6500-363) Universal mounting bracket kit (6000-535)
Temp Sensor:	Temperature Sensor with DSMT connector cable, resistance can be checked 6600-181
Hi-Limit:	Hi-Limit Sensor with DSMT connector cable, resistance can be checked 6600-179
Flow Switch:	Flow switch assembly with DSMT connector cable 6560-651
Circulation Pump:	Pump: Circ 230V 60HZ 48F 6500-913
21 Total Jets:	5-RX2 (20093-001), 15-FX (20285-001), 1-FX2-S (6541-181)
Air Controls:	2-Knob (20101-001), 2-Body and stem (6540-377)
Diverter:	1-(3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	1-75 ft ² (6540-164J), 1-40 ft ² (6473-157J), 1-Spun bound (6473-161J) Debris attachment bag: 6570-398

Year:	2012
Model:	J-LXL
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	L-LX
Board:	J-LX Series LED circuit board Board: 6600-726 Micro Chip: 6660-285 Rev. 3.61
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-LX LED 2-Pump with cable to DCU (ribbon) 6600-440
Pump #1:	2.5 HP 2-SP 240V NB 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
38 Total Stainless Steel Jets (Standard):	2-MX2 (6541-056, 6541-192), 6-NX2 (6540-815), 4-RX2 (20093-001), 23-FX (20285001), 3-FX2-S (6541-181)
Air Controls:	3 - on/off air toggle control (6541-142)
Diverter:	1 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-75 ft ² (6540-164J), 1-Skimmer Weir Filter (6540-188) Debris attachment bag: 6570-392

Year:	2012
Model:	J-LX
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	L-LX
Board:	J-LX Series LED circuit board Board: 6600-726 Micro Chip: 6660-285 Rev. 3.61
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-LX LED 2-Pump with cable to DCU (ribbon) 6600-440
Pump #1:	2.5 HP 2-SP 240V NB 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
36 Total Stainless Steel Jets (Standard):	2-MX2 (6541-056, 6541-192), 4-NX2 (6540-815), 4-RX2 (20093-001), 21-FX (20285001), 5-FX2-S (6541-181)
Air Controls:	4 - on/off air toggle control (6541-142)
Diverter:	1 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-75 ft ² (6540-164J), 1-Skimmer Weir Filter (6540-188) Debris attachment bag: 6570-392

Year:	2012
Model:	J-375
Size:	91" x 91" x 38" (231 cm x 231 cm x 96.5 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-726 Micro Chip: 6660-285 Rev. 3.61
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-300 LED 2-Pump with cable to DCU (ribbon) 2600-328
Pump #1:	2.5 HP 2-SP 240V NB 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
46 Total Textured Jets (Standard):	5-MX (6540-736, 6540-733), 12-BX (6541-230), 4-NX2 (2541-820), 21-FX (6540-555), 4-FX2-S (6541-181)
Air Controls:	4 - on/off air toggle control (6541-142)
Diverter:	2 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

Year:	2012
Model:	J-365
Size:	91" x 84" x 38" (231 cm x 213.5 cm x 96.5 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-726 Micro Chip: 6660-285 Rev. 3.61
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-300 LED 2-Pump with cable to DCU (ribbon) 2600-328
Pump #1:	2.5 HP 2-SP 240V NB 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
32 Total Textured Jets (Standard):	3-MX (6540-736, 6540-733), 23-FX (6540-555), 6-FX2-S (6541-181)
Air Controls:	5 - on/off air toggle control (6541-142)
Diverter:	2 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

Year:	2012
Model:	J-355
Size:	91" x 84" x 38" (231 cm x 213.5 cm x 96.5 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-726 Micro Chip: 6660-285 Rev. 3.61
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-300 LED 2-Pump with cable to DCU (ribbon) 2600-328
Pump #1:	2.5 HP 2-SP 240V NB 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
40 Total Textured Jets (Standard):	5-MX (6540-736, 6540-733), 12-BX (6541-230), 19-FX (6540-555), 4-FX2-S (6541-181)
Air Controls:	4 - on/off air toggle control (6541-142)
Diverter:	2 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

Year:	2012
Model:	J-345
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-726 Micro Chip: 6660-285 Rev. 3.61
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-300 LED 2-Pump with cable to DCU (ribbon) 2600-328
Pump #1:	2.5 HP 2-SP 240V NB 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-365) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
27 Total Textured Jets (Standard):	5-MX (6540-736, 6540-733), 18-FX (6540-555), 4-FX2-S (6541-181)
Air Controls:	4 - on/off air toggle control (6541-142)
Diverter:	2 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

Year:	2012
Model:	J-335
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-726 Micro Chip: 6660-285 Rev. 3.61
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5 kW 240 VAC tube heater 6500-402
Panel:	J-300 LED 2-Pump with cable to DCU (ribbon) 2600-328
Pump #1:	2.5 HP 2-SP 240V NB 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V NB 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with clear tee, curled finger end connectors 2560-040
Circulation Pump:	Pump: Circmaster 230V 60HZ 56F 6500-907
36 Total Textured Jets (Standard):	2-MX (6540-736, 6540-733), 12-BX (6541-230), 18-FX (6540-555), 4-FX2-S (6541-181)
Air Controls:	3 - on/off air toggle control (6541-142)
Diverter:	1 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

Year:	2012
Model:	J-325
Size:	76" x 84" x 34" (193 cm x 213.5 cm x 86.5 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-044 Micro Chip: 6660-285 Rev. 3.61
Transformer:	120V 12V 6560-274 (without plug) 6000-516 (with plug)
Heater:	Heater: 1.0 kW 120V/4.4kW 240 VAC tube heater (convertible) 6500-063 (1-Adapter (6540-034)
Panel:	J-300 LED 1-Pump with cable to DCU (ribbon) 2600-331
Pump #1:	1.5 HP 2-SP 120V 48F pump (6500-345) Universal mounting bracket kit (6000-532)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with tee fitting 6560-852 (2x 6540-262 adapters)
Circulation Pump:	Pump: Circ E-10 115V 60 Hz 6500-460
15 Total Textured Jets (Standard):	4-FX (6540-555), 11-FX2-S (6541-181)
Air Controls:	3 - on/off air toggle control (6541-142)
Diverter:	1 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

Year:	2012
Model:	J-315
Size:	76" x 66" x 32" (193 cm x 168 cm x 81 cm)
Series:	J-300
Board:	J-300 Series LED circuit board Board: 6600-044 Micro Chip: 6660-285 Rev. 3.61
Transformer:	120V 12V 6560-274 (without plug) 6000-516 (with plug)
Heater:	Heater: 1.0 kW 120V/4.4kW 240 VAC tube heater (convertible) 6500-063 (1-Adapter (6540-034)
Panel:	J-300 LED 1-Pump with cable to DCU (ribbon) 2600-331
Pump #1:	1.5 HP 2-SP 120V 48F pump (6500-345) Universal mounting bracket kit (6000-532)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with tee fitting 6560-852 (2x 6540-262 adapters)
Circulation Pump:	Pump: Circ E-10 115V 60 Hz 6500-460
13 Total Textured Jets (Standard):	6-FX (6540-555), 7-FX2-S (6541-181)
Air Controls:	2 - on/off air toggle control (6541-142)
Diverter:	1 - (3-way diverter) - Knob (2540-533), Cap (6540-729), Stem o-ring (2x 6540-359), Cap o-ring (6540-865), Spacer (6570-248), Gate (6540-966)
Filter:	2-60 ft ² (6000-383AJ) Debris attachment bag: 6570-392

Year:	2012
Model:	J-280
Size:	90" x 90" x 36.5" (228.6 cm x 228.6 cm x 92.7 cm)
Series:	J-200
Board:	J-200 Series LED circuit board Board: 6600-726 Micro Chip: 6660-285 Rev. 3.61
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5kW 240 VAC tube heater 6500-402
Panel:	J-200 SMT LED 2-Pump 6600-501
Pump #1:	2.5 HP 2-SP 240V 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with tee fitting 2560-040
Circulation Pump:	Pump: Circ E-10 240V 60 Hz 6000-125
44 Total Stainless Steel Jets (Standard):	8-Classic Direct (2540-265), 16-Classic Euro (2540-255), 13-Classic Luxury (2540-433), 6-Classic Mini (2540-319), 1-Classic Whirl (2540-529)
Air Controls:	4 - Knob (2540-281), Manifold (6541-284), Nut (6541-282), Gasket (6541-283)
Diverter:	1 - Knob (6540-274), Cap (2540-273), Stem o-ring (2x 6541-241), Body o-ring (6541-240), Gate (6541-242)
Filter:	1-95 ft ² (2540-381J) Debris attachment bag: 6570-392

Year:	2012
Model:	J-280
Size:	90" x 90" x 36.5" (228.6 cm x 228.6 cm x 92.7 cm)
Series:	J-200
Board:	J-200 Series LED circuit board Board: 6600-720 Micro Chip: 6660-287 Rev. 5.60
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5kW 240 VAC 6000-156
Panel:	J-200 SMT LED 2-Pump 6600-501
Pump #1:	2.5 HP 2-SP 240V 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Pressure Switch 6560-869
44 Total Stainless Steel Jets (Standard):	8-Classic Direct (2540-265), 16-Classic Euro (2540-255), 13-Classic Luxury (2540-433), 6-Classic Mini (2540-319), 1-Classic Whirl (2540-529)
Air Controls:	4 - Knob (2540-281), Manifold (6541-284), Nut (6541-282), Gasket (6541-283)
Diverter:	1 - Knob (6540-274), Cap (2540-273), Stem o-ring (2x 6541-241), Body o-ring (6541-240), Gate (6541-242)
Filter:	1-95 ft ² (2540-381J) Debris attachment bag: 6570-392

Year:	2012
Model:	J-275
Size:	90" x 90" x 36.5" (228.6 cm x 228.6 cm x 92.7 cm)
Series:	J-200
Board:	J-200 Series LED circuit board Board: 6600-720 Micro Chip: 6660-287 Rev. 5.60
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5kW 240 VAC 6000-156
Panel:	J-200 SMT LED 2-Pump 6600-501
Pump #1:	2.5 HP 2-SP 240V 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Pressure Switch 6560-869
45 Total Stainless Steel Jets (Standard):	8-Classic Direct (2540-265), 14-Classic Euro (2540-255), 12-Classic Luxury (2540-433), 3-Classic Mini (2540-319), 6-Classic Pulsator (2540-245), 2-Classic Turbo (6541-652)
Air Controls:	3 - Knob (2540-281), Manifold (6541-284), Nut (6541-282), Gasket (6541-283)
Filter:	1-50 ft ² (373045)

Year:	2012
Model:	J-270
Size:	90" x 90" x 36" (228.6 cm x 228.6 cm x 91.5 cm)
Series:	J-200
Board:	J-200 Series LED circuit board Board: 6600-720 Micro Chip: 6660-287 Rev. 5.60
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5kW 240 VAC 6000-156
Panel:	J-200 SMT LED 2-Pump 6600-501
Pump #1:	2.5 HP 2-SP 240V 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Pressure Switch 6560-869
42 Total Stainless Steel Jets (Standard):	6-Classic Direct (2540-265), 14-Classic Euro (2540-255), 10-Classic Luxury (2540-433), 7-Classic Mini (2540-319), 4-Classic Pulsator (2540-245), 1-Classic Whirl (2540-529)
Air Controls:	3 - Knob (2540-281), Manifold (6541-284), Nut (6541-282), Gasket (6541-283)
Diverter:	1 - Knob (6540-274), Cap (2540-273), Stem o-ring (2x 6541-241), Body o-ring (6541-240), Gate (6541-242)
Filter:	1-95 ft ² (2540-381J) Debris attachment bag: 6570-392

Year:	2012
Model:	J-270
Size:	90" x 90" x 36" (228.6 cm x 228.6 cm x 91.5 cm)
Series:	J-200
Board:	J-200 Series LED circuit board Board: 6600-726 Micro Chip: 6660-285 Rev. 3.61
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5kW 240 VAC tube heater 6500-402
Panel:	J-200 SMT LED 2-Pump 6600-501
Pump #1:	2.5 HP 2-SP 240V 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with tee fitting 2560-040
Circulation Pump:	Pump: Circ E-10 240V 60 Hz 6000-125
42 Total Stainless Steel Jets (Standard):	6-Classic Direct (2540-265), 14-Classic Euro (2540-255), 10-Classic Luxury (2540-433), 7-Classic Mini (2540-319), 4-Classic Pulsator (2540-245), 1-Classic Whirl (2540-529)
Air Controls:	3 - Knob (2540-281), Manifold (6541-284), Nut (6541-282), Gasket (6541-283)
Diverter:	1 - Knob (6540-274), Cap (2540-273), Stem o-ring (2x 6541-241), Body o-ring (6541-240), Gate (6541-242)
Filter:	1-95 ft ² (2540-381J) Debris attachment bag: 6570-392

Year:	2012
Model:	J-245
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	J-200
Board:	J-200 Series LED circuit board Board: 6600-720 Micro Chip: 6660-287 Rev. 5.60
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5kW 240 VAC 6000-156
Panel:	J-200 SMT LED 2-Pump 6600-501
Pump #1:	2.5 HP 2-SP 240V 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Pressure Switch 6560-869
35 Total Stainless Steel Jets (Standard):	4-Classic Direct (2540-265), 18-Classic Euro (2540-255), 9-Classic Luxury (2540-433), 2-Classic Mini (2540-319), 2-Classic Turbo (6541-652)
Air Controls:	3 - Knob (2540-281), Manifold (6541-284), Nut (6541-282), Gasket (6541-283)
Filter:	1-50 ft ² (373045)

Year:	2012
Model:	J-235
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	J-200
Board:	J-200 Series LED circuit board Board: 6600-720 Micro Chip: 6660-287 Rev. 5.60
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5kW 240 VAC 6000-156
Panel:	J-200 SMT LED 2-Pump 6600-501
Pump #1:	2.5 HP 2-SP 240V 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Pump #2:	2.5 HP 1-SP 240V 56F pump (6500-352) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Pressure Switch 6560-869
35 Total Stainless Steel Jets (Standard):	4-Classic Direct (2540-265), 12-Classic Euro (2540-255), 10-Classic Luxury (2540-433), 3-Classic Mini (2540-319), 4-Classic Pulsator (2540-245), 2-Classic Turbo (6541-652)
Air Controls:	3 - Knob (2540-281), Manifold (6541-284), Nut (6541-282), Gasket (6541-283)
Filter:	1-50 ft ² (373045)

Year:	2012
Model:	J-230
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	J-200
Board:	J-200 Series LED circuit board Board: 6600-720 Micro Chip: 6660-287 Rev. 5.60
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5kW 240 VAC 6000-156
Panel:	J-200 SMT LED 1-Pump 6600-500
Pump #1:	2.5 HP 2-SP 240V 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Pressure Switch 6560-869
25 Total Stainless Steel Jets (Standard):	7-Classic Direct (2540-265), 12-Classic Euro (2540-255), 4-Classic Mini (2540-319), 2-Classic Pulsator (2540-245)
Air Controls:	3 - Knob (2540-281), Manifold (6541-284), Nut (6541-282), Gasket (6541-283)
Diverter:	1 - Knob (6540-274), Cap (2540-273), Stem o-ring (2x 6541-241), Body o-ring (6541-240), Gate (6541-242)
Filter:	1-95 ft ² (2540-381J) Debris attachment bag: 6570-392

Year:	2012
Model:	J-230
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	J-200
Board:	J-200 Series LED circuit board Board: 6600-726 Micro Chip: 6660-285 Rev. 3.61
Transformer:	240V 12V 6560-274 (without plug) 6000-517 (with plug)
Heater:	Heater: 5.5kW 240 VAC tube heater 6500-402
Panel:	J-200 SMT LED 1-Pump 6600-500
Pump #1:	2.5 HP 2-SP 240V 56F pump (6500-367) Universal mounting bracket kit (6000-535)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Flow switch with tee fitting 2560-040
Circulation Pump:	Pump: Circ E-10 240V 60 Hz 6000-125
25 Total Stainless Steel Jets (Standard):	12-Classic Euro (2540-255), 7-Classic Luxury (2540-433), 4-Classic Mini (2540-319), 2-Classic Pulsator (2540-245)
Air Controls:	3 - Knob (2540-281), Manifold (6541-284), Nut (6541-282), Gasket (6541-283)
Diverter:	1 - Knob (6540-274), Cap (2540-273), Stem o-ring (2x 6541-241), Body o-ring (6541-240), Gate (6541-242)
Filter:	1-95 ft ² (2540-381J) Debris attachment bag: 6570-392

Year:	2012
Model:	J-210
Size:	78" Round x 36" (198 cm Round x 91.5 cm)
Series:	J-200
Board:	J-200 Series LED circuit board Board: 6600-722 Micro Chip: 6660-287 Rev. 5.60
Transformer:	240V 12V 6560-274 (without plug) 6000-516 (with plug)
Heater:	Heater: 1kW 120 VAC/4kW 240V (convertible) 6000-338
Panel:	J-200 SMT LED 1-Pump 6600-500
Pump #1:	1.5 HP 2-SP 120V 48F pump (6500-345) Universal mounting bracket kit (6000-532)
Temp Sensor:	Curled finger end connectors, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger end connectors, thermistor type, resistance can be checked 6600-144
Flow Switch:	Pressure Switch 6560-869
19 Total Textured Jets (Standard):	4-Classic Direct (2540-261), 4-Classic Luxury (2540-431), 10-Classic Mini (2540-317), 1-Divert-A-Jet (6541-800)
Air Controls:	3 - Knob (2540-281), Manifold (6541-284), Nut (6541-282), Gasket (6541-283)
Filter:	1-50 ft ² (373045)